



WEBSITE: www.abomar.com

EMAIL: sales@abomar.net

BACOLOD BRANCH

Lacson St. cor. Goldenfield St., Liroville Subd., Brgy. Singcang, Bacolod City 6100 Tel/Fax: +63 (34) 4323673 Tel/Fax:+63 (34) 4458026

CAGAYAN DE ORO BRANCH

32A G/F Neo Central Arcade, Natl. Hwy., Brgy. Cugman, Cagayan de Oro City 9000 Tel/Fax: +63 (88) 8590013

H CEBU BRANCH

111 Krizia Bldg., Gonzales Cmpd., Gorordo Ave., Brgy. Kamputhaw, Cebu City 6000 Tel: +63 (32) 2338461 Tel: +63 (32) 4171006

DAVAO BRANCH

Abomar Bldg., Balusong, Brgy. Crossing Matina 74-A, Talomo Dist. Davao City 8000 Tel: +63 (82) 2263791 Tel/Fax:+63 (82) 2210446

PASIG BRANCH

MIC-1 Manjos Industrial Compound, A. Sandoval Ave., Brgy. Pinagbuhatan Pasig City 1602 Tel: +63 (2) 86422008 Tel/Fax:+63 (2) 86409638





When it comes to keeping your machines moving, we are on it. You have no time for downtime. Let our dedicated technicians commit to lend you a hand in getting your equipment up and running.





We know our products aren't just machines - they are big investments which you depend on to be productive and efficient in the fields. That's why we put so much research and development into our maintenance product, so that your machine can deliver year after year.

Specification

Description	3036E
Engine Type	1.642 Litre, 3 Cylinder, 2800 RPM, 36hp Engine
PTO HP @ Rated RPM	28.5(21kW +/- 5%)
Fuel Injection Pump	Inline
Engine shut off	Electrical shut off
Fuel Tank Capacity	39L
Clutch Type	Single Dry Traction Clutch
Transmission Type	8Fx8R with Sync reverser
Speed	1.9 to 22.7KM (Forward and Reverse)
Rear Axle Type	Oiled
Sealings	Metal face sealing
Brake Type	Wet Disc Brakes
PTO Speed	540 RPM@ 2500 ERPM & 540E RPM @1925 ERPM
Pump Output. L / Min @ Rated	18.1
Steering L/Min	13.6
Hyd Lift Capacity, Kg @ balls	910
Selective Control Valve	Single SCV(Std)
Category	CAT-I
Steering	Power Steering
ROPS	Foldable with retractable Seat belt
Total Weight	1263Kg
Wheel Base	1574mm
Overall length (W/o Front Weight)	2919mm
Overall width	1455mm
Overall Height (with Exhaust pipe)	2105mm
Overall Height (with ROPS)	2320mm
Ground clearnce	388mm
Turning radius (with brake/W/o Brakes)	2600mm/2800mm
Front axle	MFWD
Front Tyre	8.0-16, 4PR
Rear	12.4-24, 4PR, HLD